



TIDLAND CLASS I RIGID CARTRIDGE FOR PERFORMANCE SERIES MANUAL KNIFEHOLDERS

High Side Force Slitting for 1-Inch Slit Widths

The Tidland Class I High Side Force (HSF) cartridge for Performance Series Manual knifeholders provides increased side force while maintaining a 1-inch minimum slit width. These rigid cartridges are ideal for narrow slits on materials too thick or dense for the standard Class I. The cartridges can be ordered separately for retrofit in the field, or as part of a new knifeholder assembly.





For easy installation, the Class I HSF cartridge is reversible and interchangeable with the standard shear swing cartridge. Setting the correct blade overlap is simple using the calibrated depth control knob on the Performance Series Manual control body. The pneumatic lock mount, toolless cant angle adjustment, and air-purged, dust-proof design features decrease maintenance and setup times, providing increased productivity and unrivaled finished roll quality.

GENERAL SPECIFICATIONS

Type of Slitting shear

Knifeholder Model

Performance Series Manual

Minimum Slit Width

25 mm (1.0 in)

Blade Diameter

90 mm (3.5 in)

Maximum Speed

1,000 mpm (3,500 fpm)


Side Force


~ 30% greater than a standard swing cartridge

KEY FEATURES

- · Air-purged, dust-proof design
- Calibrated depth knob for precise blade overlap adjustment
- · Toolless cant-angle selection
- Reversible, removable blade cartridge, interchangeable with standard version
- Optional pneumatic lock mount with pinion and traverse knob
- Rigid blade cartridge for increased side force (note: rigid cartridge available with manual control body only)

DESIGN FEATURES





Performance Series Manual Class I Knifeholder with Rigid Blade Cartridge Dimensions

	Α	В	C	D	E	F	G	Н	I	J	K	L	IVI	N	U	Р	Q	K
MM	120.5	62.5	1.4	97.9	91.7	73.4	26.4	46.8	123.2	168.1	16.0	100	90.0	24.0	3.0	4.8	1.3	292.4
IN	4.74	2.46	0.05	3.86	3.61	2.89	1.04	1.84	4.85	6.62	0.63	3.92	3.54	0.945	0.12	0.19	0.05	11.51



GLOBAL HEADQUARTERS AND AMERICAS

Tel +1.844.MAXCESS Fax +1.405.755.8425 sales@maxcessintl.com www.maxcessintl.com

EUROPE, MIDDLE EAST, AND AFRICA

Tel +49.6195.7002.0 Fax +49.6195.7002.933 sales@maxcess.eu www.maxcess.eu

CHINA

Tel +86.756.881.9398 Fax +86.756.881.9393 info@maxcessintl.com.cn www.maxcessintl.com.cn

INDIA

Tel +91.22.27602633 Fax +91.22.27602634 india@maxcessintl.com www.maxcess.in

JAPAN

Tel +81.43.421.1622 Fax +81.43.421.2895 japan@maxcessintl.com www.maxcess.jp

KOREA, TAIWAN, AND SE EASIA

asia@maxcessintl.com www.maxcess.asia















